

WHAT IS CLAIMED IS:

1. A hanging ring used in a curtain by punching from a metal sheet; the hanging comprising: a ring body containing a ring piece having a round hole, an extending piece one end of which extends from a periphery of the ring
5 piece and an extending bar extending from another end of the extending piece; wherein

one end of the extending bar is pressed as a rivet end for being fixed in a clip; a lateral extending frame is punched from lateral sides of the enhancing edge and the extending piece; the lateral extending frame has a non-plane
10 locking ring; a locking hole is punched from the plane locking ring; the non plane locking ring is twisted through an angle so that it is at different orientation from the other part of the lateral extending frame; and

an inner wall of the locking hole is a threaded wall, for locking a screw rod of a decoration.

15 2. The hanging ring used in a curtain as claimed in claim 1, wherein an upper lateral side of the ring piece is formed with a front side concave cambered surface and a lower lateral side of the ring piece is formed with a back side concave cambered surface; an outer lateral side of the front side concave cambered surface is chamfered as a plan inclined surface and an
20 outer lateral side of the back side concave cambered surface is also chamfered surface as a plane inclined surface; the two inclined surface of the front side concave cambered surface and back side concave cambered surface are formed with an enhancing edge so as to enhance the strength and tolerance of the ring body.

25 3. The hanging ring used in a curtain as claimed in claim 1, wherein the

extending piece has at least one through hole for receiving a rope.